



ALL VOLTAGES MEASURED UNDER FOLLOWING CONDITIONS:
 1 - USE OF 11 MEGOHMS INPUT IMPEDANCE VTVM. VOLTMETER.
 2 - ALL VOLTAGES $\pm 10\%$ WITH RESPECT TO GROUND.
 3 - A.C. INPUT AT 117 V. 50-60 CPS.
 4 - NO SIGNAL AT ANTENNA AND OTHER INPUT TERMINALS.
 5 - FRONT PANEL CONTROLS AT:
 MODE SELECTOR - MONO.
 VOLUME CONTROL - MAX.
 MUTING - OFF

UNLESS OTHERWISE SPECIFIED
 ALL RESISTORS 1/2 W 20%
 ALL CAPACITORS IN PF
 ALL INDUCTORS IN MICRO H
 FM. IF: 10.7 MC

SYMBOL NUMBERS NOT USED
 R 80 C 28
 R 87 C 33
 C 35

FOR SERIAL NUMBERS 22T04 AND ABOVE

SCHEMATIC, MR67		PART NO.
McIntosh LABORATORY INC. 2 Chambers St. Binghamton, N. Y.	USED ON:	
TOLERANCES - unless otherwise specified - 1% resistors, 5% capacitors, 1% inductors	SCALE: 1/8" = 1"	DATE: 1, 4, 63
	DESIGN: 18	APP: SAC
		SC123-176